



SWIFTEC
 Castlepoint, Castle Way,
 Ellon, Aberdeenshire,
 AB419RG, SCOTLAND
 TEL +44 (0)1358 720888
 FAX +44 (0)1358 720880
 e-mail stratec@swiftec.co.uk

STRATEC®
G30PP
GEOGRID

A SWIFTEC® GROUP BRAND NAME



Technical Specification

Quality:

The Stratec brand is a new name built on 30 years experience of tried and proven geoproducts for the civil engineering industry. Products are manufactured to extremely high specifications and are fully backed to ISO 9001 standards.

Benefits:

The Stratec range includes woven and non woven geotextiles, geogrids, erosion control products and other geoproducts for use in all aspects of groundworks and civil engineering.

Supply:

Stratec® products are mostly available for direct delivery to site or yard via our bulk distribution warehouse.

Installation:

Full installation guidelines are available

Typical Specification:

'Where directed all areas must be covered with Stratec® G30PP Polypropylene Geogrids with a Tensile Strength of 30kN in both directions. The material must be installed in accordance with the supplier's recommendations Available from Swiftec, Castlepoint, Ellon, AB41 9RG, Tel 01358 720888, Fax 01358 720880, stratec@swiftec.co.uk

| Specification: | | |
|---------------------------------|------|---------------|
| Grade | | G30PP |
| Product Code | | - |
| Raw Material | | Polypropylene |
| Colour | | Black |
| Mesh Size MD/CD | mm | 40/41 |
| Tensile Strength MD/CD EN 10319 | kN/m | 30/30 |
| Strength at 2% MD/CD EN 10319 | kN/m | 11/11 |
| Strength at 5% MD/CD EN 10319 | kN/m | 21/21 |
| Roll Length | m | 50 |
| Roll Width | m | 4 |

Please contact our sales office on Tel 01358 720888, Fax 01358 720880 or email stratec@swiftec.co.uk

These properties are the manufacturer's typical values based on the average of several tests. As the installation and handling of this product are beyond our control, the user must ensure that the product is suitable for the application. Swiftec cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. E & OE.